

SILOVAC 100 HV AD

CENTRAL VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS



- ✓ Balanced flap discharge system
- ✓ Easy and quick big-bag bagging.
- ✓ Large capacity detachable container. Forklift intakes.

Suction Unit

Power supply	V - Hz	230 - 50 1~
Power	kW	2 x 1,6
Maximum depression	mmH2O	3600
Maximum air flow rate	m3/h	340
Nozzle	mm	80
Noisiness (EN ISO 3744)	dB(A)	78

Filter Unit

Surface area - diameter	cm ² -mm	20.000 - 420
-------------------------	---------------------	--------------

Collection unit

Capacity	lt	100
----------	----	-----

Encumbrances

Dimensions	cm	139x126x294h
Weight	kg	160

APPLICATIONS:



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

SILOVAC 100 HV AD

CENTRAL VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS

FILTER UNIT

The filter can be cleaned by means of the integrated mechanical cleaning system: an external filter shaking lever shakes the filter with a vertical movement, ensuring an effective and safe cleaning action, maintaining constant suction power and preventing the dispersion of dust into the environment.

COLLECTION UNIT

The material is unloaded directly into big-bags.