Fumebuster AC – Activated Carbon Welding Vacuum Cleaner

AIR FILTRATION SOLUTIONS



- Ompressed air supply via 2 Venturi units

Suction Unit		
Power supply	V - Hz	400 - 50 3~
Power	kW	1,5
Maximum air flow rate	m3/h	1300
Nozzle	mm	150
Noisiness (EN ISO 3744)	dB(A)	72
Filter Unit		
Cleaning system		Handbook
Filtration efficiency		F9 95%
Collection unit		
Capacity	lt	200
Liquid capacity	lt	50
Collection container		Painted
Cyclonic unit		Integrated
Exhaust system		Disposable bag
Encumbrances		
Dimensions	cm	65 x 75 x 129h
Weight	kg	131

APPLICATIONS:



Fumebuster AC – Activated Carbon Welding Vacuum Cleaner

AIR FILTRATION SOLUTIONS

SUCTION UNIT

It is equipped with an electric fan that provides a high airflow, ideal for direct extraction of volatile chips generated by machine tool processes or suspended dust present in work environments.

FILTER UNIT

The vacuum cleaner is equipped with a progressive filtration consisting of panel filters with 4 stages of filtration.

COLLECTION UNIT

Container made entirely of AISI 316 stainless steel

OPTIONALS

- Local remote start-up
- Local/remote control
- Stainless steel chamber

