# Fumebuster AC – Activated Carbon Welding Vacuum Cleaner

**AIR FILTRATION SOLUTIONS** 



- Ompressed air supply via 2 Venturi units

Suction Unit		
Power supply	V - Hz	400 - 50 3~
Power	kW	1,5
Maximum air flow rate	m3/h	1300
Nozzle	mm	150
Noisiness (EN ISO 3744)	dB(A)	72
Filter Unit		
Cleaning system		Handbook
Filtration efficiency		F9 95%
Collection unit		
Collection container		Painted
Cyclonic unit		Integrated
Exhaust system		Disposable bag
Encumbrances		
Dimensions	cm	65 x 75 x 129h
Weight	kg	131

**APPLICATIONS:** 



## Fumebuster AC – Activated Carbon Welding Vacuum Cleaner

**AIR FILTRATION SOLUTIONS** 

## **SUCTION UNIT**

It is equipped with an electric fan that provides a high airflow, ideal for direct extraction of volatile chips generated by machine tool processes or suspended dust present in work environments.

#### **FILTER UNIT**

The vacuum cleaner is equipped with a progressive filtration consisting of panel filters with 4 stages of filtration.

## **COLLECTION UNIT**

Container made entirely of AISI 316 stainless steel

## **OPTIONALS**

- Local remote start-up
- Local/remote control
- Stainless steel chamber

