

# Fumebuster H – Fume extractor with hepa filter

AIR FILTRATION SOLUTIONS



## Suction Unit

Power supply	V - Hz	400 - 50 3~
Power	kW	1,1
Maximum air flow rate	m3/h	1300
Nozzle	mm	150
Construction		Painted Steel
Noisiness (EN ISO 3744)	dB(A)	72

## Filter Unit

Filtration efficiency		H13 99,95%
-----------------------	--	------------

## Collection unit

Collection container		Painted
----------------------	--	---------

## Encumbrances

Dimensions	cm	65 x 75 x 113h
Weight	kg	123

APPLICATIONS: Mechanical industry Steel mills and foundries



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# Fumbuster H – Fume extractor with hepa filter

AIR FILTRATION SOLUTIONS

## **SUCTION UNIT**

---

It is equipped with an electric fan that provides a high airflow, ideal for direct extraction of volatile chips generated by machine tool processes or suspended dust present in work environments.

## **FILTER UNIT**

---

The vacuum cleaner is equipped with a progressive filtration consisting of panel filters with 4 stages of filtration.