## PROVAC 150 D







- O Accessories included, ideal for cleaning professionals.
- Sector Extremely silent.
- Ocompact and portable industrial vacuum cleaner.

Suction Unit		
Power supply	V - Hz	230 - 50 1~
Power	kW	0,9
Maximum depression	mmH2O	1.900
Maximum air flow rate	m3/h	180
Noisiness (EN ISO 3744)	dB(A)	64
Filter Unit		
Primary filter		Sack
Total filter surface area	cm <sup>2</sup>	1.000
Filter media - class	IEC 60335-2-69	Polyester L
Cleaning system		Handbook
Collection unit		
Dust capacity	lt	15
Encumbrances		
Dimensions	cm	38x34x44h
Weight	kg	8

INDUSTRIAL VACUUMS

APPLICATIONS:

All data mentioned in this document may change without notice. Tutti i dati in questo documento potrebbero variare senza preavviso. www.dupuyvacuums.com info@dupuy.it

# PROVAC 150 D

#### **INDUSTRIAL VACUUMS**

#### **SUCTION UNIT**

Suction is generated by one carbon brush by-pass motor activated by independent switches located on a solid metal head that protects the motor from possible blows and ingress of external bodies, keeping the noise level to a minimum.

### **FILTER UNIT**

The polyester bag filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.



All data mentioned in this document may change without notice. Tutti i dati in questo documento potrebbero variare senza preavviso. www.dupuyvacuums.com info@dupuy.it