

# W1 WALL MOUNTED industrial vacuum cleaner for dust, solids and liquids with wall mounting

## INDUSTRIAL VACUUMS



- ✓ 100% steel construction.
- ✓ Simultaneous vacuuming of dust, liquids and solids.
- ✓ Large surface filter for fine dust with integrated manual cleaning system.
- ✓ Easy-to-empty detachable container.

### Suction Unit

Power supply	V - Hz	230 - 50 ~ 1
Power	kW	1,1
Maximum depression	mmH2O	2.400
Maximum air flow rate	m3/h	180
Noisiness (EN ISO 3744)	dB(A)	76

### Filter Unit

Primary filter		Pockets
Surface area - diameter	cm <sup>2</sup> -mm	8.000 - 280
Filter media - class	IEC 60335-2-69	Polyester L
Cleaning system		Handbook

### Collection unit

Capacity	lt	15 l
Collection system		Release container

### Encumbrances

Dimensions	cm	43x40x96h
Weight	kg	76

## APPLICATIONS:



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# W1 WALL MOUNTED industrial vacuum cleaner for dust, solids and liquids with wall mounting

INDUSTRIAL VACUUMS

## SUCTION UNIT

## FILTER UNIT

The polyester pocket filter is located inside the steel filtering chamber and protects the suction unit, ensuring high dust retention and purity of the exhaust air thanks to its large surface area and high filtration efficiency. A manual cleaning system, consisting of a vertically moving filter shaker, allows the operator to clean the filter effortlessly at any time, extending the filter's life and preventing it from becoming saturated and reducing suction power. The suction system positioned below the filter allows the simultaneous suction of dust, solids and liquids without the need to replace or remove the filter.

## COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

## OPTIONALS

- ✓ Hepa absolute filter /h14
- ✓ Stainless steel container and filter chamber
- ✓ Earthing
- ✓ NOMEX heat-resistant filter up to 200°C
- ✓ Steel ring for suction into disposable bags
- ✓ Hydro-oleophobic filter class m
- ✓ Antistatic filter class m
- ✓ Ptfе-treated filter class m