

Dedust 50 PRO Z22 high airflow industrial vacuum cleaner

INDUSTRIAL VACUUMS



- Large surface filter for fine dust with integrated manual cleaning system.
- Compact and portable industrial vacuum cleaner.
- The inside of the filter chamber is ATEX Z20 certified; the outside of the machine is Z22 certified

Suction Unit

ATEX Zones	Zone 22 Powders	
Power supply	V - Hz	400 - 50 3~
Power	kW	4
Maximum depression	mmH2O	370
Maximum air flow rate	m ³ /h	3.500
Nozzle	mm	200
Noisiness (EN ISO 3744)	dB(A)	74

Filter Unit

Primary filter	Pockets	
Total filter surface area	cm ²	50.000
Filter media - class	IEC 60335-2-69	Polyester ANT M
Cleaning system	Handbook	
Absolute filter	Incluso	

Collection unit

Capacity	lt	100
----------	----	-----

Encumbrances

Dimensions	cm	80x132x232h
Weight	kg	145

APPLICATIONS:



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

Dedust 50 PRO Z22 high airflow industrial vacuum cleaner

INDUSTRIAL VACUUMS

SUCTION UNIT

It is equipped with an electric fan that provides a high airflow, ideal for direct extraction of volatile chips generated by machine tool processes or suspended dust present in work environments.

FILTER UNIT

The filter can be cleaned by means of the integrated mechanical cleaning system: an external filter shaking lever shakes the filter with a vertical movement, ensuring an effective and safe cleaning action, maintaining constant suction power and preventing the dispersion of dust into the environment.

COLLECTION UNIT

The all-steel, epoxy-polyester powder-coated frame is supplied in a fixed-floor version.

OPTIONALS

- Stainless steel chamber
- Local remote start-up
- Ptfe-treated filter class m