SILOVAC 600 PRO ACD suction silos for large quantities of dust and solids

INDUSTRIAL VACUUMS







- Integrated filter cleaning system
- Easy and quick big-bag bagging.
- Material discharge with tilting door, butterfly valve, sliding damper or rotovalve.

Suction Unit		
Power supply	V - Hz	400 - 50 3~
Zone use		Hazardous location
EX Category		CE ACD
Power	kW	8,6-12,6
Maximum depression	mmH2O	2.700-2.900
Maximum air flow rate	m3/h	700-1100
Electrical protection	IP	65
Nozzle	mm	80
Noisiness (EN ISO 3744)	dB(A)	77
Filter Unit		
Primary filter		Pockets
Surface area - diameter	cm^2-mm	50.000 - 560
Total filter surface area	cm^2	52.000-103.000
Filter media - class	IEC 60335-2-69	M ANT
Absolute filter		Incluso
Collection unit		
Capacity	lt	600
Encumbrances		
Weight	kg	500

APPLICATIONS: **Food, chemical and pharmaceutical industry** **Sandblasting** **Glass** **Mechanical industry** **Steel mills and foundries**

DUPUY

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

SILOVAC 600 PRO ACD suction silos for large quantities of dust and solids

INDUSTRIAL VACUUMS

SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

FILTER UNIT

Inside the steel filter chamber is the antistatic polyester pocket filter, which protects the suction unit and prevents the risk of sparks due to static energy build-up.

COLLECTION UNIT

The material is unloaded directly into big-bags.

OPTIONALS

- Other filter media available upon request