


ACD industrial vacuum cleaners for fine dust with reverse-air filter cleaning

INDUSTRIAL VACUUMS



- ✓ ACD classification for vacuuming combustible dust in non-classified zones
- ✓ Maintenance-free motor suitable for continuous operation.

Suction Unit

EX Category		CE ACD
Power	kW	4,6 - 8,6
Maximum depression	mmH2O	2.600-4.000
Maximum air flow rate	m3/h	420-700
Electrical protection	IP	55

Filter Unit

Primary filter		Cartridge
Surface area - diameter	cm ² -mm	80.000 - 150
Number of cartridges		3
Filter media - class	IEC 60335-2-69	M ANT
Cleaning system		Automatic PN countercurrent air
Absolute filter		Standard

Collection unit

Capacity	lt	100
----------	----	-----

Encumbrances

Dimensions	cm	119x65x180h
Weight	kg	138 - 183

APPLICATIONS:



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

ACD industrial vacuum cleaners for fine dust with reverse-air filter cleaning

INDUSTRIAL VACUUMS

FILTER UNIT

The cartridges are automatically cleaned by an automatic, timed and alternate pneumatic reverse air cleaning system. The air supply is provided by a compressor that can be installed (on request) on the rear fairing.

COLLECTION UNIT

The vacuumed material is collected in a stainless steel container, mounted on a tilting trolley.

OPTIONALS

- ✓ Ptfе-treated filter class m