WD 3000 industrial wet and dry vacuum cleaner

INDUSTRIAL VACUUMS









- Accessories included, ideal for cleaning professionals.
- 100% steel construction.
- Simultaneous vacuuming of dust, liquids and solids.
- Liquid level monitored by a floating device to stop when the container is full.
- Tilting container for easy emptying.

Suction Unit		
Power supply	V - Hz	230 - 50 ~ 1
Power	kW	2 x 1,1
Maximum depression	mmH2O	2.400
Maximum air flow rate	m3/h	360
Nozzle	mm	50
Noisiness (EN ISO 3744)	dB(A)	78
Filter Unit		
Primary filter		Sack
Surface area - diameter	cm^2-mm	5.000 - 420
Filter media - class	IEC 60335-2-69	Polyester L
Cleaning system		Handbook
Collection unit		
Capacity	lt	60
Float		Mechanic
Collection system		Tipping container
Encumbrances		
Dimensions	cm	62x60x100h
Weight	kg	32

APPLICATIONS: **General housekeeping** **Food, chemical and pharmaceutical industry**

DUPUY

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

WD 3000 industrial wet and dry vacuum cleaner

SUCTION UNIT

Suction is generated by two carbon brush by-pass motors activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

FILTER UNIT

The polyester bag filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuumed material is collected in a steel hopper container with an electro-pneumatically controlled swing door for quick discharge.