

Oilvac 500

INDUSTRIAL VACUUM CLEANERS



- ✓ Designed for complete cleaning of CNC machines, all in one vacuum.

Suction unit

Voltage	V - Hz	400 - 50 3~
Power	kW	4
Max waterlift	mmH2O	3.200
Continuous water lift	mmH2O	2.400
Max air flow	m3/h	420
Relief valve		Integrated
Noise level (EN ISO 3744)	dB(A)	75

Filtering Unit

Cleaning system	Manual
Filter for oil/chips separation	TNT sheet

Collection unit

Powder capacity	lt	75
Liquid capacity	lt	500
Floating device		Electric
Collection system		Removable drawer
Discharge system		Submersible pump

Encumbrances

Dimensions	cm	182x101x134h
Weight	kg	520

APPLICATIONS: Mechanical industry



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

FILTERING UNIT

Solids and chips are separated in an integrated container, whereas liquids are purified by means of a NW filter cloth.

COLLECTION UNIT

Possibility of cleaning the emptied tank with an adjustable high-pressure lance.

Independent 200l/min pump for re-injecting the emulsifier into the tank.