# SK on-board vacuum unit for industry

INDUSTRIAL VACUUMS




Maintenance-free motor suitable for continuous operation.

| | | |
|---|---|---|
| **Suction Unit** | | |
| Power supply | V - Hz | 400 - 50 ~ 3 |
| Power | kW | 0,85 - 4,6 |
| Maximum depression | mmH2O | 3.200 - 2.000 |
| Maximum air flow rate | m3/h | 450 - 150 |
| Nozzle | mm | 50 |
| Construction | | Stainless Steel AISI304 |
| Noisiness (EN ISO 3744) | dB(A) | 70 - 73 |
| **Filter Unit** | | |
| Primary filter | | Pockets |
| Surface area - diameter | $cm^2$-mm | 8.000 - 280 |
| Filter media - class | IEC 60335-2-69 | Polyester ANT M |
| Cleaning system | | Handbook |
| **Collection unit** | | |
| Capacity | lt | 25 |
| Collection system | | Tipping container |
| **Encumbrances** | | |
| Dimensions | cm | 77 x 45 x 60h |
| Weight | kg | 35 - 58 |

**APPLICATIONS:** **Glass** **Food, chemical and pharmaceutical industry**

DUPUY

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

**www.dupuyvacuums.com**
**info@dupuy.it**

# SK on-board vacuum unit for industry

INDUSTRIAL VACUUMS

## SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

## FILTER UNIT

The antistatic polyester stellar filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

## OPTIONALS

- Earthing