

# SK on-board vacuum unit for industry

## INDUSTRIAL VACUUMS



- ✓ Maintenance-free motor suitable for continuous operation.

### Suction Unit

Power supply	V - Hz	400 - 50 ~ 3
Power	kW	0,85 - 4
Maximum depression	mmH2O	3.200 - 2.000
Maximum air flow rate	m3/h	450 - 150
Nozzle	mm	50
Construction		Stainless Steel AISI304
Noisiness (EN ISO 3744)	dB(A)	70 - 73

### Filter Unit

Primary filter		Pockets
Surface area - diameter	cm <sup>2</sup> -mm	8.000 - 280
Filter media - class	IEC 60335-2-69	Polyester ANT M
Cleaning system		Handbook

### Collection unit

Capacity	lt	25
Collection system		Tipping container

### Encumbrances

Dimensions	cm	77 x 45 x 60h
Weight	kg	35 - 58

APPLICATIONS: Glass



Food, chemical and pharmaceutical industry



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# SK on-board vacuum unit for industry

INDUSTRIAL VACUUMS

## SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

## FILTER UNIT

The antistatic polyester stellar filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

## OPTIONALS

✓ Earthing