

Chipvac 400 oil and chip vacuum with tilting discharge

INDUSTRIAL VACUUMS



- ✓ Large capacity tilting vacuum cleaner for solids and liquids. Designed to make simplify the vacuuming of large quantities of different materials.
- ✓ Possibility of turning upside down from 50° to 90° with the help of a forklift truck. Simple and effective DU-PUY patent system.

Suction Unit

Power supply	V - Hz	400 - 50 3~
Power	kW	7,5 - 12,5
Maximum depression	mmH2O	4.400 - 4.000
Continuous depression	mmH2O	2.900 - 2.700
Maximum air flow rate	m3/h	1.100 - 700
Nozzle	mm	80
Noisiness (EN ISO 3744)	dB(A)	74

Filter Unit

Primary filter		Pockets
Surface area - diameter	cm ² -mm	30.000 - 560
Filter media - class	IEC 60335-2-69	Polyester L
Cleaning system		Handbook

Collection unit

Dust capacity	lt	400
Exhaust system		Tipping container

Encumbrances

Dimensions	cm	147x105x207h
Weight	kg	490 - 555

APPLICATIONS: Mechanical industry Glass



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

Chipvac 400 oil and chip vacuum with tilting discharge

INDUSTRIAL VACUUMS

SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

FILTER UNIT

The polyester star filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuum cleaner is mounted on a sturdy metal frame and fitted with heavy-duty industrial wheels for easy manoeuvrability also on uneven surfaces.

The container is compact and contains a sieve grid to separate the solids.

OPTIONALS

- ✓ Oil-proof seal
- ✓ Hydro-oleophobic filter class m
- ✓ Oil-chip separation grid