

Chipvac 400

INDUSTRIAL VACUUM CLEANERS



- ✓ Large capacity tilting vacuum cleaner for solids and liquids. Designed to make simplify the vacuuming of large quantities of different materials.
- ✓ Possibility of turning upside down from 50° to 90° with the help of a forklift truck. Simple and effective DU-PUY patent system.

Suction unit

Voltage	V - Hz	400 - 50 3~
Power	kW	7,5 - 12,5
Max waterlift	mmH2O	4.400 - 4.000
Continuous water lift	mmH2O	2.900 - 2.700
Max air flow	m3/h	1.100 - 700
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	74

Filtering Unit

Primary filter		Star
Surface - Diameter	cm ² -mm	30.000 - 560
Material - Efficiency	IEC 60335-2-69	Polyester L
Cleaning system		Manual

Collection unit

Powder capacity	lt	400
Discharge system		Tilting container

Encumbrances

Dimensions	cm	147x105x207h
Weight	kg	490 - 555

APPLICATIONS: Mechanical industry Glass



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

Chipvac 400

INDUSTRIAL VACUUM CLEANERS

SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

FILTERING UNIT

The polyester star filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuum cleaner is mounted on a sturdy metal frame and fitted with heavy-duty industrial wheels for easy manoeuvrability also on uneven surfaces.

The container is compact and contains a sieve grid to separate the solids.

OPTIONALS

- ✓ Oil-proof seal
- ✓ Hydro-oleophobic filter class m
- ✓ Oil-chip separation grid