

CVAC Fixed vacuum unit for central system

CENTRAL VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS



- ✓ Equipped as standard with an electrical panel with star-delta starting and local/remote control, pressure relief valve and soundproofing guard.

Suction unit

Voltage	V - Hz	400 - 50 ~ 3
Power	kW	7.5 - 18.5
Max waterlift	mmH2O	4.000 - 4.500
Continuous water lift	mmH2O	2.600 - 3.200
Max air flow	m3/h	750 - 1.350
Relief valve		Integrated
Suction inlet	mm	100
Construction		Painted steel
Noise level (EN ISO 3744)	dB(A)	74 - 81

Filtering Unit

Cleaning system	Manual
-----------------	--------

Collection unit

Encumbrances

Dimensions	cm	89 x 78 x 124h
------------	----	----------------

APPLICATIONS: Sandblasting



Food, chemical and pharmaceutical industry

Cementitious

Steel mills and foundries

Mechanical industry



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

CVAC Fixed vacuum unit for central system

CENTRAL VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS

SUCTION UNIT

It is supplied complete with electrical panel for starting up the suction unit and with sequencer board for managing cartridge cleaning cycles.

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

OPTIONALS

- ✓ Additional silencer
- ✓ Hepa safety filter h14 103,000cm2
- ✓ Inverter