

CVAC central vacuum cleaner for centralized systems

CENTRALIZED VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS



- ✓ Equipped as standard with an electrical panel with star-delta starting and local/remote control, pressure relief valve and soundproofing guard.

Suction Unit

Power supply	V - Hz	400 - 50 ~ 3
Power	kW	7.5 - 18.5
Maximum depression	mmH2O	4.000 - 4.500
Continuous depression	mmH2O	2.600 - 3.200
Maximum air flow rate	m3/h	750 - 1.350
Limiting valve		Integrated
Nozzle	mm	100
Construction		Painted Steel
Noisiness (EN ISO 3744)	dB(A)	74 - 81

Filter Unit

Cleaning system	Handbook
-----------------	----------

Collection unit

Encumbrances

Dimensions	cm	89 x 78 x 124h
------------	----	----------------

APPLICATIONS: Sandblasting  Food, chemical and pharmaceutical industry  Cementitious  Steel mills and foundries  Mechanical industry



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

CVAC central vacuum cleaner for centralized systems

CENTRALIZED VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS

SUCTION UNIT

It is supplied complete with electrical panel for starting up the suction unit and with sequencer board for managing cartridge cleaning cycles.

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

OPTIONALS

- ✓ Additional silencer
- ✓ Hepa safety filter h14 103,000cm2
- ✓ Inverter