SKY 1000 – 1500 Oil mist collectors





Reduced	d energy	consumption
---------	----------	-------------

- Quick and easy maintenance.
- **⊘** Easy installation on the machine.
- **⊘** Quick and easy filter replacement system.

Suction Unit		
Power supply	V - Hz	400 - 50 ~ 3
Power	kW	0,37 - 0,55
Maximum air flow rate	m3/h	1000 - 1500
Nozzle	mm	150
Construction		Painted Steel
Noisiness (EN ISO 3744)	dB(A)	64
Filter Unit		
Surface area - diameter	cm²-mm	3.000/60.000 - 310/350
Cleaning system		Handbook
Filter media - class	EN 1822-5	G3-G4 o M
Filter type		Multilayer or Cartridge
Collection unit		
Cyclonic unit		Integrated
Encumbrances		
Dimensions	cm	Ø49 x 54h
Weight	kg	30 - 33

APPLICATIONS:



SKY 1000 – 1500 Oil mist collectors

AIR FILTRATION SOLUTIONS

SUCTION UNIT

The suction unit is a low-power, low-consumption, high airflow blower.

FILTER UNIT

Versatility of filtration: multi-layer filter (standard) or pleated cartridge with a high filtration surface area and a coalescing pre-filter

COLLECTION UNIT

Vacuumed and filtered oils and emulsions settle on the wall of the vacuum cleaner and can be recovered through the discharge hose.

OPTIONALS

- Installation kit with riser
- Wall mounting kit.
- Installation kit with adjustable riser
- Cyclone pre-filter kit.
- Adjustable column for floor fixing from 1.5 to 2.5 m.

