

W2 AIR Air operated industrial vacuum cleaner

INDUSTRIAL VACUUM CLEANERS



- ✓ 100% steel construction.
- ✓ Compressed air supply via a Venturi unit

Suction unit

Max waterlift	mmH2O	3.700
Max air flow	m3/h	300 - 150
Suction inlet	mm	50
Construction		Painted steel
Noise level (EN ISO 3744)	dB(A)	78
Air supply	nlt/min (nm ³ /h)	729 - 1458
Air supply pressure	bar	6
Air supply hose	mm	12

Filtering Unit


Primary filter		Star
Surface - Diameter	cm ² -mm	20000 - 420
Material - Efficiency	IEC 60335-2-69	Polyester L
Cleaning system		Manual

Collection unit

Capacity	lt	40
Collection system		Release container

Encumbrances

Dimensions	cm	63 x 57 x 108h
Weight	kg	42 - 43

APPLICATIONS:  General housekeeping Sandblasting

 **DUPUY**

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

W2 AIR Air operated industrial vacuum cleaner

INDUSTRIAL VACUUM CLEANERS

SUCTION UNIT

Suction is generated by one Venturi air vacuum unit enclosed in a solid steel head containing sound-absorbing material. This minimises noise during operation.

FILTERING UNIT

The polyester star filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

OPTIONALS

- ✔ Hepa absolute filter /h14