


W2 AIR Air operated industrial vacuum cleaner

INDUSTRIAL VACUUMS



- ✓ 100% steel construction.
- ✓ Compressed air supply via a Venturi unit

Suction Unit

| | | |
|-------------------------|------------------------------|---------------|
| Maximum depression | mmH2O | 3.700 |
| Maximum air flow rate | m3/h | 300 - 150 |
| Nozzle | mm | 50 |
| Construction | | Painted Steel |
| Noisiness (EN ISO 3744) | dB(A) | 78 |
| Air supply | nlt/min (nm ³ /h) | 729 - 1458 |
| Air supply pressure | bar | 6 |
| Air supply hose | mm | 12 |

Filter Unit


| | | |
|-------------------------|---------------------|-------------|
| Primary filter | | Pockets |
| Surface area - diameter | cm ² -mm | 20000 - 420 |
| Filter media - class | IEC 60335-2-69 | Polyester L |
| Cleaning system | | Handbook |

Collection unit

| | | |
|-------------------|----|-------------------|
| Capacity | lt | 40 |
| Collection system | | Release container |

Encumbrances

| | | |
|------------|----|----------------|
| Dimensions | cm | 63 x 57 x 108h |
| Weight | kg | 42 - 43 |

APPLICATIONS:  General housekeeping Sandblasting

 **DUPUY**

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

W2 AIR Air operated industrial vacuum cleaner

INDUSTRIAL VACUUMS

SUCTION UNIT

Suction is generated by one Venturi air vacuum unit enclosed in a solid steel head containing sound-absorbing material. This minimises noise during operation.

FILTER UNIT

The polyester star filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

OPTIONALS

- Hepa absolute filter /h14