

W2 AIR Venturi Aspirator

INDUSTRIAL VACUUMS



- 100% steel construction.
- Compressed air supply via a Venturi unit

Suction Unit

Maximum depression	mmH2O	3.700
Maximum air flow rate	m ³ /h	300 - 150
Nozzle	mm	50
Construction		Painted Steel
Noisiness (EN ISO 3744)	dB(A)	78
Air supply	nlt/min (nm ³ /h)	729 - 1458
Air supply pressure	bar	6
Air supply hose	mm	12

Filter Unit

Primary filter	Pockets
Surface area - diameter	cm ² -mm
Filter media - class	IEC 60335-2-69
Cleaning system	Handbook

Collection unit

Capacity	lt	40
Collection system		Release container

Encumbrances

Dimensions	cm	63 x 57 x 108h
Weight	kg	42 - 43

APPLICATIONS:  General housekeeping Sandblasting

 DUPUY

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

W2 AIR Venturi Aspirator

INDUSTRIAL VACUUMS

SUCTION UNIT

Suction is generated by one Venturi air vacuum unit enclosed in a solid steel head containing sound-absorbing material. This minimises noise during operation.

FILTER UNIT

The polyester star filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

OPTIONALS

Hepa absolute filter /h14