
W3 AIR

INDUSTRIAL VACUUMS







- 100% steel construction.
- Large surface filter for fine dust with integrated manual cleaning system.
- Simultaneous vacuuming of dust, liquids and solids.
- Easy-to-empty detachable container.
- Compressed air supply via 2 Venturi units

Suction Unit		
Maximum depression	mmH2O	5.000
Maximum air flow rate	m3/h	465 - 590
Nozzle	mm	80
Construction		Painted Steel
Noisiness (EN ISO 3744)	dB(A)	79
Air supply	nlt/min (nm^3/h)	1.530 - 2.500
Filter Unit		
Primary filter		Pockets
Surface area - diameter	cm^2-mm	20.000 - 420
Filter media - class	IEC 60335-2-69	Polyester L
Cleaning system		Handbook
Collection unit		
Capacity	lt	65 - 100
Collection system		Release container
Encumbrances		
Dimensions	cm	70x62x134h
Weight	kg	65 - 66

APPLICATIONS: **Sandblasting** **General housekeeping** **Glass**

DUPUY

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

W3 AIR

INDUSTRIAL VACUUMS

SUCTION UNIT

Suction is generated by two Venturi air vacuum units enclosed in a solid steel head containing sound-absorbing material. This minimises noise during operation.

FILTER UNIT

The polyester filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

OPTIONALS

- Ø50 WD accessory kit
- Ø50 Dry accessory kit

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it