



- ✓ Simultaneous vacuuming of dust, liquids and solids.
- ✓ Large surface filter for fine dust with integrated manual cleaning system.
- ✓ Large capacity detachable container. Forklift intakes.

Suction Unit

Maximum depression	mmH2O	7.000
Maximum air flow rate	m3/h	760
Noisiness (EN ISO 3744)	dB(A)	79
Air supply	nlt/min (nm ³ /h)	2.800 (168)

Filter Unit

Primary filter		Pockets
Surface area - diameter	cm ² -mm	50.000 - 560
Filter media - class	IEC 60335-2-69	Polyester L
Cleaning system		Handbook

Collection unit

Capacity	lt	160/120
Collection container		Stainless Steel AISI304
Collection system		Release container

Encumbrances

APPLICATIONS: Glass  General housekeeping  Food, chemical and pharmaceutical industry  Sandblasting

SUCTION UNIT

Suction is generated by one Venturi air vacuum unit enclosed in a solid steel head containing sound-absorbing material. This minimises noise during operation.

FILTER UNIT

The filter can be cleaned by means of the integrated mechanical cleaning system: an external filter shaking lever shakes the filter with a vertical movement, ensuring an effective and safe cleaning action, maintaining constant suction power and preventing the dispersion of dust into the environment.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

OPTIONALS

- ✓ Large surface filter cat. m ptfе
- ✓ Abrasion proof plate in Hardox steel for filter chamber
- ✓ Forklift intakes