

M90 Industrial vacuum cleaner with side channel blower

INDUSTRIAL VACUUMS



- ✓ Extremely silent.
- ✓ Release container with the possibility of using disposable bags.
- ✓ Simultaneous vacuuming of dust, liquids and solids.
- ✓ Large surface filter for fine dust with integrated manual cleaning system.
- ✓ Maintenance-free motor suitable for continuous operation.

Suction Unit

| | | |
|-------------------------|--------|-------------|
| Power supply | V - Hz | 400 - 50 3~ |
| Power | kW | 7,5 |
| Maximum depression | mmH2O | 4.000 |
| Continuous depression | mmH2O | 2.700 |
| Maximum air flow rate | m3/h | 700 |
| Limiting valve | | Integrated |
| Nozzle | mm | 80 |
| Noisiness (EN ISO 3744) | dB(A) | 77 |

Filter Unit

| | | |
|-------------------------|---------------------|--------------|
| Primary filter | | Pockets |
| Surface area - diameter | cm ² -mm | 35.000 - 420 |
| Filter media - class | IEC 60335-2-69 | Polyester L |
| Cleaning system | | Handbook |

Collection unit

| | | |
|-------------------|----|-------------------|
| Capacity | lt | 100 |
| Collection system | | Release container |

Encumbrances

| | | |
|------------|----|-------------|
| Dimensions | cm | 119x65x180h |
| Weight | kg | 182 |

APPLICATIONS: Glass Mechanical industry



General housekeeping



Food, chemical and pharmaceutical industry

DUPUY

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

M90 Industrial vacuum cleaner with side channel blower

INDUSTRIAL VACUUMS

SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

FILTER UNIT

The antistatic polyester pocket filter is located inside the steel filtering chamber and protects the suction unit, ensuring high dust retention and purity of the exhaust air thanks to its large surface area and high filtration efficiency. A manual cleaning system, consisting of a vertically moving filter shaker, allows the operator to clean the filter effortlessly at any time, extending the filter's life and preventing it from becoming saturated and reducing suction power. The suction system positioned below the filter allows the simultaneous suction of dust, solids and liquids without the need to replace or remove the filter.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

OPTIONALS

- ✓ Nomex filter - heat resistant up to 250°
- ✓ Hepa absolute filter /h14
- ✓ Large surface filter cat. m ptfе
- ✓ Stainless steel chamber
- ✓ Earthing
- ✓ Cyclone for filter protection
- ✓ Additional silencer
- ✓ Forklift intakes