CVAC 50-70-90 central vacuum cleaners for centralized systems

CENTRALIZED VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS





Suction Unit		
Power supply	V - Hz	400 - 50 ~ 3
Power	kW	4,6 - 8,6
Maximum depression	mmH2O	3.200 - 3.600
Continuous depression	mmH2O	2.600 - 3.200
Maximum air flow rate	m3/h	420 - 700
Limiting valve		Integrated
Nozzle	mm	60 - 70
Construction		Painted Steel
Noisiness (EN ISO 3744)	dB(A)	74 - 77
Filter Unit		
Cleaning system		Handbook
Collection unit		
Encumbrances		
Dimensions	cm	67 x 63 x 131h

APPLICATIONS: CEMENT PLANTS Food, chemical and pharmaceutical industry Glass Steel mills and foundries Sandblasting

DUPUY

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

CVAC 50-70-90 central vacuum cleaners for centralized systems

SUCTION UNIT

It is supplied complete with electrical panel for starting up the suction unit and with sequencer board for managing cartridge cleaning cycles.

A pressure relief valve protects the motor from overheating, ensuring the supply of air for cooling.

OPTIONALS

- Additional silencer
- Inverter