

CVAC Fixed suction unit for vacuuming systems

CENTRAL VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS



Suction Unit

Power supply	V - Hz	400 - 50 ~ 3
Power	kW	4 - 7,5
Maximum depression	mmH2O	3.200 - 3.600
Continuous depression	mmH2O	2.600 - 3.000
Maximum air flow rate	m3/h	420 - 700
Limiting valve		Integrated
Nozzle	mm	60 - 70
Construction		Painted Steel
Noisiness (EN ISO 3744)	dB(A)	74 - 77

Filter Unit

Cleaning system	Handbook
-----------------	----------

Collection unit

Encumbrances

Dimensions	cm	67 x 63 x 131h
------------	----	----------------

APPLICATIONS: Cementitious



Food, chemical and pharmaceutical industry

Glass

Steel mills and foundries

Sandblasting



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

CVAC Fixed suction unit for vacuuming systems

CENTRAL VACUUM SYSTEMS – CENTRAL VACUUM UNITS AND FILTER SILOS

SUCTION UNIT

It is supplied complete with electrical panel for starting up the suction unit and with sequencer board for managing cartridge cleaning cycles.

A pressure relief valve protects the motor from overheating, ensuring the supply of air for cooling.

OPTIONALS

- ✓ Additional silencer
- ✓ Inverter