Oilvac 200





- Save money by recovering and reusing cutting oil and emulsion.
- ✓ Large grid basket to collect metal chips and oil microfiltration filters to remove dust and metal particles.
- ✓ Liquid level monitored by a floating device to stop when the container is full.

Suction Unit		
Power supply	V - Hz	230 - 50 1~
Power	kW	3 x 1,1 - 2 x 1,6
Maximum depression	mmH2O	2.400
Maximum air flow rate	m3/h	540
Nozzle	mm	50
Noisiness (EN ISO 3744)	dB(A)	78
Filter Unit		
Primary filter		Pockets
Surface area - diameter	cm²-mm	14.000 - 420
Filter media - class	IEC 60335-2-69	M ANT Hydro-oleo repellent
Collection unit		
Dust capacity	lt	30
Liquid capacity	lt	200
Float		Electric
Exhaust system		Immersion pump
Encumbrances		
Dimensions	cm	122x62x130h

APPLICATIONS: Mechanical industry

All data mentioned in this document may change without notice. Tutti i dati in questo documento potrebbero variare senza preavviso.

kg

Weight

www.dupuyvacuums.com info@dupuy.it

205

INDUSTRIAL VACUUMS

Oilvac 200

INDUSTRIAL VACUUMS

SUCTION UNIT

Suction is generated by three carbon brush by-pass motors activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

FILTER UNIT

A float stops the suction when the liquid in the container reaches the maximum level, preventing spillage.

The polyester star filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuum cleaner is mounted on a sturdy metal frame and fitted with heavy-duty industrial wheels for easy manoeuvrability also on uneven surfaces.

OPTIONALS

Ppl oil filtration kit up to 100 microns (suction)

DUPUY

All data mentioned in this document may change without notice. Tutti i dati in questo documento potrebbero variare senza preavviso. www.dupuyvacuums.com info@dupuy.it