

# W2 single phase industrial vacuum cleaner

INDUSTRIAL VACUUMS



- ✓ Accessories included, ideal for cleaning professionals.
- ✓ 100% steel construction.
- ✓ Simultaneous vacuuming of dust, liquids and solids.

## Suction Unit

Power supply	V - Hz	230 - 50 1~
Power	kW	2 x 1,1
Maximum depression	mmH2O	2.400
Maximum air flow rate	m3/h	360
Nozzle	mm	50
Noisiness (EN ISO 3744)	dB(A)	78

## Filter Unit


Primary filter		Pockets
Surface area - diameter	cm <sup>2</sup> -mm	20.000 - 420
Cleaning system		Handbook

## Collection unit

Capacity	lt	40
Collection system		Release container

## Encumbrances

Dimensions	cm	63x57x116h
Weight	kg	44

APPLICATIONS: Mechanical industry   Glass   Wood and plastic    General housekeeping    Food, chemical and pharmaceutical industry



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# W2 single phase industrial vacuum cleaner

INDUSTRIAL VACUUMS

## SUCTION UNIT

Suction is generated by two carbon brush by-pass motors activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

## FILTER UNIT

The antistatic polyester stellar filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

The filter can be cleaned by means of the integrated mechanical cleaning system: an external filter shaking lever shakes the filter with a vertical movement, ensuring an effective and safe cleaning action, maintaining constant suction power and preventing the dispersion of dust into the environment.

## COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

## OPTIONALS

- ✓ Nomex filter - heat resistant up to 250°
- ✓ Hepa absolute filter /h14
- ✓ Accessory basket
- ✓ Ptfе-treated filter class m
- ✓ Hydro-oleophobic filter class m
- ✓ Antistatic filter class l
- ✓ Antistatic filter class m
- ✓ Stainless steel container and filter chamber
- ✓ Stainless steel container
- ✓ Earthing
- ✓ Local remote start-up