# Privato: W2 Infini Z22 Atex certified industrial vacuum cleaner with turbine

## **INDUSTRIAL VACUUMS**





- Ø Release container with the possibility of using disposable bags.
- Ø Filter with large surface area.
- Ø Maintenance-free motor suitable for continuous operation.
- Ø Simultaneous vacuuming of dust, liquids and solids.

Suction Unit		
Power supply	V - Hz	230 - 50 1~
Power	kW	1,8
Maximum depression	mmH2O	2.300
Maximum air flow rate	m3/h	250
Nozzle	mm	50
Noisiness (EN ISO 3744)	dB(A)	74
Filter Unit		
Primary filter		Pockets
Surface area - diameter	cm²-mm	20.000 - 420
Filter media - class	IEC 60335-2-69	Polyester L
Cleaning system		Handbook
Collection unit		
Capacity	lt	40
Collection system		Release container
Encumbrances		
Dimensions	cm	63x58x130h
Weight	kg	58

### APPLICATIONS: Mechanical industry Glass Woo

Glass Wood and plastic

General housekeeping

ŧ.

Food, chemical and pharmaceutical industry

# 

All data mentioned in this document may change without notice. Tutti i dati in questo documento potrebbero variare senza preavviso. www.dupuyvacuums.com info@dupuy.it

# Privato: W2 Infini Z22 Atex certified industrial vacuum cleaner with turbine

### **INDUSTRIAL VACUUMS**

### SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

# **FILTER UNIT**

The filter can be cleaned by means of the integrated mechanical cleaning system: an external filter shaking lever shakes the filter with a vertical movement, ensuring an effective and safe cleaning action, maintaining constant suction power and preventing the dispersion of dust into the environment.

The polyester star filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

# **COLLECTION UNIT**

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

### **OPTIONALS**

### Accessory basket

- Pressure relief valve
- 🧭 Antistatic filter class m
- Antistatic filter class l
- Hydro-oleophobic filter class m
- Optimization Ptfe-treated filter class m
- Nomex filter heat resistant up to 250°
- 🧭 🛛 Stainless steel container and filter chamber
- 🥝 Stainless steel container
- Zearthing
- 🥝 🛛 Local remote start-up



All data mentioned in this document may change without notice. Tutti i dati in questo documento potrebbero variare senza preavviso. www.dupuyvacuums.com info@dupuy.it