

WD 4500

INDUSTRIAL VACUUMS



- ✓ 100% steel construction.
- ✓ Simultaneous vacuuming of dust, liquids and solids.
- ✓ Liquid level monitored by a floating device to stop when the container is full.
- ✓ Tilting container for easy emptying.

Suction Unit

Power supply	V - Hz	230 - 50 1~
Power	kW	3 x 1,1
Maximum depression	mmH2O	2.400
Maximum air flow rate	m3/h	540
Nozzle	mm	80
Noisiness (EN ISO 3744)	dB(A)	78

Filter Unit

Primary filter		Sack
Surface area - diameter	cm ² -mm	5.000 - 460
Filter media - class	IEC 60335-2-69	Polyester L
Cleaning system		Handbook

Collection unit

Capacity	lt	100
Float		Mechanic
Collection system		Tipping container
Exhaust system		Exhaust valve

Encumbrances

Dimensions	cm	76x76x108h
Weight	kg	37

APPLICATIONS:  General housekeeping



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

SUCTION UNIT

Suction is generated by three carbon brush by-pass motors activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

FILTER UNIT

The polyester bag filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuumed material is collected in a stainless steel container, mounted on a tilting trolley.

Thanks to an discharge valve, the container can be emptied conveniently and quickly.