

CVAC Z22 ATEX

INDUSTRIAL VACUUM CLEANERS



Suction unit

Atex zones	Zone 22 Dust	
Voltage	V - Hz	400 - 50 ~ 3
Marking	Ex II 3D Ex tc IIIB T135°C X Dc	
Usage area	Hazardous location	
Power	kW	4 - 25
Max waterlift	mmH2O	4.400 - 2.600
Max air flow	m3/h	1.350 - 420
Relief valve	Integrated	
Noise level (EN ISO 3744)	dB(A)	74 - 81

Filtering Unit

Cleaning system	Manual
-----------------	--------

Collection unit

Encumbrances

APPLICATIONS: Cementitious  Food, chemical and pharmaceutical industry Sandblasting Steel mills and foundries



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

CVAC Z22 ATEX

INDUSTRIAL VACUUM CLEANERS

SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

OPTIONALS

- ✓ Additional silencer
- ✓ Inverter
- ✓ Hepa safety filter h14 103,000cm²
- ✓ Hepa safety filter h14 52,000cm²