Oilvac 600HV system for treating metal shavings and oil

INDUSTRIAL VACUUMS







- Large grid basket for metal chips collection with easy tilting discharge system.
- Chip separation basket.
- Three-phase oil and chip vacuum cleaner with discharge pump.
- Save money by recovering and reusing cutting oil and emulsion.

Suction Unit		
Power supply	V - Hz	400 - 50 3~
Power	kW	12,6
Maximum depression	mmH2O	4.700
Continuous depression	mmH2O	4.300
Maximum air flow rate	m3/h	520
Limiting valve		Integrated
Nozzle	mm	50
Filter Unit		
Primary filter		Pockets
Surface area - diameter	cm^2-mm	14.000 - 420
Filter media - class	IEC 60335-2-69	M ANT Hydro-oleo repellent
Cleaning system		Handbook
Collection unit		
Dust capacity	lt	65
Liquid capacity	lt	600
Float		Electric
Encumbrances		
Dimensions	cm	180x85x205h
Weight	kg	415

APPLICATIONS: **Mechanical industry**

DUPUY

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

Oilvac 600HV system for treating metal shavings and oil

INDUSTRIAL VACUUMS

SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor shaft and the impeller. Since it has no transmission systems, it requires no routine maintenance, is suitable for long term continuous operation and provides superior suction performance.

FILTER UNIT

The vacuum cleaner is equipped with a chip container with a grid basket to separate solids (chips, metal swarf) from liquids. The container can be tilted by means of a crank handle, allowing chips to be discharged safely, conveniently and quickly.

COLLECTION UNIT

Thanks to an electric pump, the vacuumed liquid can be quickly disposed of or re-injected.

OPTIONALS

- Ppl oil filtration kit up to 100 microns (suction)

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it