

- The inside of the filter chamber is ATEX Z20 certified; the outside of the machine is Z22 certified
- Compliance to EN IEC 62784:2018 for zone 22

Suction Unit			
Power supply	V - Hz	230 - 50 ~ 1	
Marking	II 1/3D Ex h tb IIIC T80° (int)/T9	II 1/3D Ex h tb IIIC T80° (int)/T95°C (ext) Da/Dc	
Zone use		Hazardous location	
EX Category		CE EX 22 1/3D	
Power	kW	1,1	
Maximum depression	mmH2O	2.400	
Maximum air flow rate	m3/h	180	
Noisiness (EN ISO 3744)	dB(A)	76	
Filter Unit			
Primary filter		Pockets	
Surface area - diameter	cm <sup>2</sup> -mm	8.000 - 280	
Filter media - class	IEC 60335-2-69	Polyester ANT M	
Cleaning system		Handbook	
Collection unit			
Capacity	lt	15	
Collection container		Stainless Steel AISI304	
Collection system		Release container	
Encumbrances			
Dimensions	cm	43x40x96h	
147-1-1-1	1	22	



APPLICATIONS: Food, chemical and pharmaceutical industry



## W1 1/3D – Compact and versatile industrial vacuum cleaner

**INDUSTRIAL VACUUMS** 

## **SUCTION UNIT**

Suction is generated by one carbon brush by-pass motor activated by independent switches located on a solid metal head that protects the motor from possible blows and ingress of external bodies, keeping the noise level to a minimum.

## **FILTER UNIT**

Inside the steel filter chamber is the antistatic polyester pocket filter, which protects the suction unit and prevents the risk of sparks due to static energy build-up. An absolute filter (99.995% of 0.18 micron, Class H) is included to ensure the retention of the finest dust and the purity of the exhaust air.

## **COLLECTION UNIT**

The vacuumed material is collected in a stainless steel container, mounted on wheels, which allows for quick and clean disposal.

