

W1 1/3D ATEX vacuum cleaner for solid powders and liquids

INDUSTRIAL VACUUMS



- ✓ The inside of the filter chamber is ATEX Z20 certified; the outside of the machine is Z22 certified
- ✓ Compliance to EN IEC 62784:2018 for zone 22

Suction Unit

Power supply	V - Hz	230 - 50 ~ 1
Marking	II 1/3D Ex h tb IIIC T80° (int)/T95°C (ext) Da/Dc	
Zone use	Hazardous location	
EX Category	CE EX 22 1/3D	
Power	kW	1,1
Maximum depression	mmH2O	2.400
Maximum air flow rate	m3/h	180
Noisiness (EN ISO 3744)	dB(A)	76

Filter Unit


Primary filter	Pockets	
Surface area - diameter	cm ² -mm	8.000 - 280
Filter media - class	IEC 60335-2-69	Polyester ANT M
Cleaning system	Handbook	

Collection unit

Capacity	lt	15
Collection container	Stainless Steel AISI304	
Collection system	Release container	

Encumbrances

Dimensions	cm	43x40x96h
Weight	kg	22

APPLICATIONS:  Food, chemical and pharmaceutical industry



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

W1 1/3D ATEX vacuum cleaner for solid powders and liquids

INDUSTRIAL VACUUMS

SUCTION UNIT

Suction is generated by one carbon brush by-pass motor activated by independent switches located on a solid metal head that protects the motor from possible blows and ingress of external bodies, keeping the noise level to a minimum.

FILTER UNIT

Inside the steel filter chamber is the antistatic polyester pocket filter, which protects the suction unit and prevents the risk of sparks due to static energy build-up. An absolute filter (99.995% of 0.18 micron, Class H) is included to ensure the retention of the finest dust and the purity of the exhaust air.

COLLECTION UNIT

The vacuumed material is collected in a stainless steel container, mounted on wheels, which allows for quick and clean disposal.