# W1 AIR-EX 1/2D – ATEX certified industrial compressed air vacuum cleaner

### **INDUSTRIAL VACUUMS**



Compressed	lair	supply via	a	Venturi unit
------------	------	------------	---	--------------

- Ompact and portable industrial vacuum cleaner.
- ♦ The inside of the filter chamber is ATEX Z20 certified; the outside of the machine is Z21 certified
- 100% steel construction.

Suction Unit		
Zone use		Hazardous location
EX Category		CE EX 21 1/2D
Maximum depression	mmH2O	3.700
Maximum air flow rate	m3/h	150 - 300
Noisiness (EN ISO 3744)	dB(A)	78
Air supply	nlt/min (nm³/h)	729 (43) - 1458 (87)
Air supply pressure	bar	6
Filter Unit		
Primary filter		Pockets
Surface area - diameter	cm²-mm	8.000-280
Filter media - class	IEC 60335-2-69	M ANT
Cleaning system		Handbook
Filtration efficiency		
Absolute filter		Standard
Surface area - diameter	cm²-mm	11.000
Collection unit		
Capacity	lt	15
Collection system		Release container
Encumbrances		
Disconsissor		424000 -

**APPLICATIONS:** 



## W1 AIR-EX 1/2D – ATEX certified industrial compressed air vacuum cleaner

**INDUSTRIAL VACUUMS** 

## **SUCTION UNIT**

Suction is generated by one Venturi air vacuum unit enclosed in a solid steel head containing sound-absorbing material. This minimises noise during operation.

### **FILTER UNIT**

Inside the steel filter chamber is the antistatic polyester pocket filter, which protects the suction unit and prevents the risk of sparks due to static energy build-up. An absolute filter (99.995% of 0.18 micron, Class H) is included to ensure the retention of the finest dust and the purity of the exhaust air.

## **COLLECTION UNIT**

The vacuumed material is collected in a stainless steel container, mounted on wheels, which allows for quick and clean disposal.

