

# WD 3000 AIR Z22

## INDUSTRIAL VACUUM CLEANERS



### Suction unit

Voltage	V - Hz	729 (43)
Marking	II 1/2D Ex h IIC T85° C Da/Db - II 2/2G Ex h IIB T6 Gb/Gb	
EX category		CE EX 21 1/2D
Max waterlift	mmH2O	3.700
Max air flow	m3/h	150
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	78
Air supply pressure	bar	6
Air supply hose	mm	12

### Filtering Unit

Primary filter		Bag
Surface - Diameter	cm <sup>2</sup> -mm	8.000-420
Total filtering surface area	cm <sup>2</sup>	8.000
Material - Efficiency	IEC 60335-2-69	M ANT
Cleaning system		Manual
Filtration efficiency		
Primary filter		Standard

### Collection unit

Capacity	lt	60
----------	----	----

### Encumbrances

Weight	kg	37
--------	----	----

## APPLICATIONS:



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# WD 3000 AIR Z22

INDUSTRIAL VACUUM CLEANERS

## **SUCTION UNIT**

---

Suction is generated by two Venturi air vacuum units enclosed in a solid steel head containing sound-absorbing material. This minimises noise during operation.

## **FILTERING UNIT**

---

The polyester bag filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

## **COLLECTION UNIT**

---

The vacuumed material is collected in a stainless steel container, mounted on wheels, which allows for quick and clean disposal.