

W2 EX1/3D – ATEX-certified industrial vacuum cleaner for medium explosion risk zones

INDUSTRIAL VACUUMS



- ✓ The inside of the filter chamber is ATEX Z20 certified; the outside of the machine is Z22 certified

Suction Unit

Power supply	V - Hz	230 - 50/60 1~
Marking	II 1/3D Ex h tb IIIC T80° (int)/T95°C (ext) Da/Dc	
Zone use	Hazardous location	
EX Category	CE EX 22 1/3D	
Power	kW	1 x 1,1 by-pass
Maximum depression	mmH2O	2.400
Maximum air flow rate	m3/h	180
Noisiness (EN ISO 3744)	dB(A)	76

Filter Unit

Primary filter	Pockets	
Surface area - diameter	cm ² -mm	20.000 - 420
Total filter surface area	cm ²	11.000
Cleaning system	Handbook	
Filtration efficiency	M ANT	
Absolute filter	Standard	
Filter class		

Collection unit

Capacity	lt	40
Collection container	Stainless Steel AISI304	

Encumbrances

Weight	kg	49
--------	----	----

APPLICATIONS:



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

W2 EX1/3D – ATEX-certified industrial vacuum cleaner for medium explosion risk zones

INDUSTRIAL VACUUMS

SUCTION UNIT

Suction is generated by one carbon brush by-pass motor activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

FILTER UNIT

Inside the steel filter chamber is the antistatic polyester pocket filter, which protects the suction unit and prevents the risk of sparks due to static energy build-up. An absolute filter (99.995% of 0.18 micron, Class H) is included to ensure the retention of the finest dust and the purity of the exhaust air.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.