W2 ACD – ACD industrial vacuum cleaner for non-continuous applications in non-ATEX zones

INDUSTRIAL VACUUMS



- ACD classification for vacuuming combustible dust in non-classified zones

Suction Unit		
Power supply	V - Hz	230 - 50/60 1~
Zone use		Ordinary location
EX Category		CE ACD
Power	kW	2 x 1,1 bypass
Maximum depression	mmH2O	2.460
Maximum air flow rate	m3/h	360
Noisiness (EN ISO 3744)	dB(A)	76

Filter Unit		
Primary filter		Pockets
Surface area - diameter	cm^2-mm	20.000 - 420
Cleaning system		Handbook
Filtration efficiency		M ANT
Absolute filter		Standard
Filter class		

Collection unit		
Capacity	lt	40
Collection container		Painted

Encumbrances		
Dimensions	cm	63x57x116h

APPLICATIONS:

W2 ACD – ACD industrial vacuum cleaner for non-continuous applications in non-ATEX zones

SUCTION UNIT

FILTER UNIT

Inside the steel filter chamber is the antistatic polyester pocket filter, which protects the suction unit and prevents the risk of sparks due to static energy build-up. An absolute filter (99.995% of 0.18 micron, Class H) is included to ensure the retention of the finest dust and the purity of the exhaust air.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it