

# W2 1/2D – ATEX-certified industrial vacuum cleaner for areas with high explosion risk

## INDUSTRIAL VACUUMS



- ✓ The inside of the filter chamber is ATEX Z20 certified; the outside of the machine is Z21 certified

### Suction Unit

Power supply	V - Hz	230 - 50/60 1~
Marking	II 1/2D Ex h tb IIIC T80° (int)/T95°C (ext) Da/Db	
Zone use	Hazardous location	
EX Category	CE EX 21 1/2D	
Power	kW	1 x 1,1 brushless
Maximum depression	mmH2O	2250
Maximum air flow rate	m3/h	215
Noisiness (EN ISO 3744)	dB(A)	74

### Filter Unit

Primary filter	Pockets	
Surface area - diameter	cm <sup>2</sup> -mm	20.000 - 420
Total filter surface area	cm <sup>2</sup>	11.000
Cleaning system	Handbook	
Filtration efficiency	M ANT	
Absolute filter	Standard	
Filter class		

### Collection unit

Capacity	lt	40
----------	----	----

### Encumbrances

Dimensions	mm	630x570x1200
------------	----	--------------

## APPLICATIONS:



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# W2 1/2D – ATEX-certified industrial vacuum cleaner for areas with high explosion risk

INDUSTRIAL VACUUMS

## **SUCTION UNIT**

---

Suction is generated by one carbon brush by-pass motor activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

## **FILTER UNIT**

---

Inside the steel filter chamber is the antistatic polyester pocket filter, which protects the suction unit and prevents the risk of sparks due to static energy build-up. An absolute filter (99.995% of 0.18 micron, Class H) is included to ensure the retention of the finest dust and the purity of the exhaust air.

## **COLLECTION UNIT**

---

The vacuumed material is collected in a stainless steel container, mounted on wheels, which allows for quick and clean disposal.