

W1 AIR-EX 1/3D – ATEX certified industrial compressed air vacuum cleaner

INDUSTRIAL VACUUMS



- ✓ Compressed air supply via a Venturi unit
- ✓ The inside of the filter chamber is ATEX Z20 certified; the outside of the machine is Z22 certified
- ✓ 100% steel construction.

Suction Unit

Marking	1/3 D Ex h IIIC T80°C Da/Dc	
Zone use		Hazardous location
EX Category		CE EX 22 1/3D
Maximum depression	mmH2O	3.700
Maximum air flow rate	m3/h	150-300
Noisiness (EN ISO 3744)	dB(A)	78
Air supply	nlt/min (nm ³ /h)	729 (43) -1458 (87)
Air supply pressure	bar	6

Filter Unit


Primary filter		Pockets
Total filter surface area	cm ²	8.000-280
Filter media - class	IEC 60335-2-69	M ANT
Cleaning system		Handbook
Filtration efficiency		

Collection unit

Capacity	lt	15
Collection system		Release container

Encumbrances

Dimensions	cm	43x40x98h
Weight	kg	22-25

APPLICATIONS:  Food, chemical and pharmaceutical industry Sandblasting



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

W1 AIR-EX 1/3D – ATEX certified industrial compressed air vacuum cleaner

INDUSTRIAL VACUUMS

SUCTION UNIT

Suction is generated by one Venturi air vacuum unit enclosed in a solid steel head containing sound-absorbing material. This minimises noise during operation.

FILTER UNIT

Inside the steel filter chamber is the antistatic polyester pocket filter, which protects the suction unit and prevents the risk of sparks due to static energy build-up. An absolute filter (99.995% of 0.18 micron, Class H) is included to ensure the retention of the finest dust and the purity of the exhaust air.

COLLECTION UNIT

The vacuumed material is collected in a stainless steel detachable container, mounted on wheels, which allows for quick and clean disposal. Bagging is also possible.