

# Oilvac 130P

## INDUSTRIAL VACUUM CLEANERS



- ✓ Large grid basket to collect metal chips and oil microfiltration filters to remove dust and metal particles.

### Suction unit

Voltage	V - Hz	230 - 50 1~
Power	kW	3 x 1,1
Max waterlift	mmH2O	2.400
Max air flow	m3/h	540
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	78

### Filtering Unit

Primary filter		Star
Surface - Diameter	cm <sup>2</sup> -mm	14.000 - 420
Material - Efficiency	IEC 60335-2-69	M ANT Water-oil repellent

### Collection unit

Powder capacity	lt	30
Liquid capacity	lt	130
Floating device		Electric
Discharge system		Electric Pump 100mt/lt

### Encumbrances

Dimensions	cm	70x62x144h
Weight	kg	90

**APPLICATIONS:** Mechanical industry



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# Oilvac 130P

## INDUSTRIAL VACUUM CLEANERS

### SUCTION UNIT

Suction is generated by three carbon brush by-pass motors activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

### FILTERING UNIT

The suction nozzle is tangential and the internally welded cyclone promotes partial suppression of the extracted dust and chips, ensuring excellent filter protection.

### COLLECTION UNIT

Finer chips are retained by an additional basket fitted with a PPL filter which removes any impurities from the oil/emulsion.

A grid basket inside the container separates solids (chips, metal swarf) from liquids, which drain to the bottom of the container. The liquid is quickly disposed of via a manual liquid drain valve.

### OPTIONALS

- ✓ Ppl oil filtration kit up to 100 microns (suction)