M70-90 ACD vacuums combustible dust liquid solids in unclassified areas

INDUSTRIAL VACUUMS





- ACD classification for vacuuming combustible dust in non-classified zones

Suction Unit		
Power supply	V - Hz	400 - 50 3~
EX Category		CE ACD
Power	kW	6,3 - 8,6
Maximum depression	mmH2O	3.200 - 2.900
Maximum air flow rate	m3/h	530 - 700
Electrical protection	IP	65
Noisiness (EN ISO 3744)	dB(A)	74 - 77

Filter Unit		
Primary filter		Pockets
Surface area - diameter	cm^2-mm	35.000 - 420
Total filter surface area	cm^2	26.000 - 52.000
Filter media - class	IEC 60335-2-69	M ANT

Collection unit		
Capacity	lt	100

Encumbrances		
Dimensions	cm	119x65x180h
Weight	kg	150 - 183

APPLICATIONS: Sandblasting

M70-90 ACD vacuums combustible dust liquid solids in unclassified areas

FILTER UNIT

The filter can be cleaned by means of the integrated mechanical cleaning system: an external filter shaking lever shakes the filter with a vertical movement, ensuring an effective and safe cleaning action, maintaining constant suction power and preventing the dispersion of dust into the environment.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

OPTIONALS

- Star-delta starter panel board

All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it