

M70-90 ACD vacuums combustible dust liquid solids in unclassified areas

INDUSTRIAL VACUUMS



- ✓ ACD classification for vacuuming combustible dust in non-classified zones

Suction Unit

Power supply	V - Hz	400 - 50 3~
Power	kW	5,5 - 7,5
Maximum depression	mmH2O	3.000 - 2.700
Maximum air flow rate	m3/h	530 - 700
Electrical protection	IP	65
Nozzle	mm	80
Noisiness (EN ISO 3744)	dB(A)	74 - 77

Filter Unit

Primary filter		Pockets
Surface area - diameter	cm ² -mm	35.000 - 420
Total filter surface area	cm ²	26.000 - 52.000
Filter media - class	IEC 60335-2-69	M ANT

Collection unit

Capacity	lt	100
----------	----	-----

Encumbrances

Dimensions	cm	119x65x180h
Weight	kg	150 - 183

APPLICATIONS: Sandblasting



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

M70-90 ACD vacuums combustible dust liquid solids in unclassified areas

INDUSTRIAL VACUUMS

FILTER UNIT

The filter can be cleaned by means of the integrated mechanical cleaning system: an external filter shaking lever shakes the filter with a vertical movement, ensuring an effective and safe cleaning action, maintaining constant suction power and preventing the dispersion of dust into the environment.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.

OPTIONALS

- ✔ Star-delta starter panel board